



(12) UK Patent (19) GB (11) 2 337 113 (13) B

(54) Title of Invention

Laboratory in a disk

(51) INT CL¹; G01N 33/487

(21) Application No
9920550.2

(22) Date of filing
27.02.1998

(30) Priority Data

(31) 60039419

(32) 28.02.1997

(33) US

(86) International Application Data
PCT/US98/04377
En 27.02.1998

(87) International Publication Data
WO98/38510
En 03.09.1998

(43) Application published
10.11.1999

(45) Patent published
21.03.2001

(72) Inventor(s)
Jorma Virtanen

(73) Proprietor(s)
Burstin Laboratories Inc

(Incorporated in USA -
California)

33601 Avenida Calita
San Juan Capistrano
California 92675
United States of America

(74) Agent and/or
Address for Service
D Young & Co
21 New Fetter Lane
London
EC4A 1DA
United Kingdom



(52) Domestic classification
(Edition S)
G1A AA4 APG ARF AR7
AT21
G1B BCB

(56) Documents cited
EP0721016 A1
EP0707076 A1
EP0417305 A1
WO98/01533 A1
WO96/35940 A1
WO96/32841 A1

(continued on next page)

GB 2 337 113 B - continuation

- (56) Documents cited (cont'd)
W096/09548 A1
W093/22053 A1
W093/20092 A1
Carol T Schembri et al,
"Portable simultaneous
multiple analyte whole
blood for point-of-care
testing", Clinical Chemistry
vol. 38, no. 9, September
1992, pages 1665-1670.
- (58) Field of search
As for published application
2337113 A viz:
INT CL⁶ C12Q, G01N
updated as appropriate



2/14

FIG. 2B





FIG. 3



3/14

FIG. 4




FIG. 5




FIG. 6




FIG. 7







FIG. 8





SAMPLE IN



SAMPLE OUT

FIG. 10




FIG. 11A




FIG. 11B





FIG. 11C



9/14

FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14a




FIG. 14b




FIG. 14c




FIG. 14d




FIG. 14e




FIG. 14e




FIG. 15A





FIG. 15B



CUVETTE ASSEMBLY

FIG. 16






FIG. 17



LABORATORY IN A DISK

FIELD OF THE INVENTION

This invention relates generally to diagnostic assays and methodology therefor. In particular, it relates to diagnostic assay components configured on a compact optical disk and methodology for the use thereof.

BACKGROUND

There is an enormous need to make clinical assays faster, cheaper and simpler to perform. Ideally patients should be able to test themselves, if so desired. One way towards this goal has been through miniaturization and integration of various assay operations. Currently, a number of bio-chip assays (so-called because some are built using silicon chip photolithography techniques) are commercially available or under development. All of these approaches require a reading machine and a computer.

Disk-shaped cassettes used for clinical assays in conjunction with UV/Vis spectrometry are also commercially available. U.S. Patent No. 5,122,284 describes a centrifugal rotor that contains a number of interconnected fluid chambers connected to a plurality of cuvettes. The rotor is adapted to be utilized with a conventional laboratory centrifuge, and is formed of materials that allow photometric detection of the results of assays that have been carried out in the reaction cuvettes. A large number of rotor configurations and related apparatus for the same or similar types of analysis have been described. See for example U.S. Patents 5,472,603; 5,173,193; 5,061,381; 5,304,348; 5, 518,930; 5,457,053; 5,409,665; 5,160,702; 5,173,262; 5,409,665; 5,591,643; 5,186,844; 5,122,284; 5,242,606; and patents listed therein. Lyophilized reagents for use in such systems are described in U.S. Patent 5,413,732.

The principles of a centrifugal analyzer have been adapted into a disk that can be used in a CD-drive like instrument (Mian, et al., WO 97/21090 Application). Mian

teaches a modified CD-drive with a dual function: 1. It is used to read information stored in the disk, and 2. It is used to rotate the disk. However, Mian does not teach utilization of the reading capability of a CD-drive for actual assay analysis.

Notwithstanding recent advances, there remains a need for a simpler assay configuration that performs assays quickly, efficiently, accurately and at low cost. The present invention combines diagnostic assays with computers and compact disk technology. In its most preferred embodiment, a computer with a compact disk reader is the only instrument needed. All chemistry is performed inside a compact disk that may be referred to as an integrated biocompact disk (IBCD). The same compact disk is also encoded with software, i.e., machine-readable instructional and control information, that provides instructions to a computer prior to, during and after the assay.

CDs or DVDs represent the most economical and in many ways best information storage media. It must be noted that CD and DVD are currently used acronyms that may change in the future even if the underlying technology stays basically the same. A CD- or DVD-drive is in several respects equivalent to a scanning confocal microscope. At the same time these instruments are comparable to good centrifuges, because in commercial drives the rotation frequency is between 200-12,000 rpm and can be adjusted within certain limits. Combining these three features into the same analytical system results into great simplification as compared with any other analytical technique. Yet, the performance is comparable or better than in most competing methods. Although this invention requires slightly modified CD- or DVD-drives, it is possible to incorporate these changes into commercial drives. This will enable Point-Of-Patient-Care (POPC) and home use of this invention. Use of CD- or DVD-drives will allow accurate digital analysis of any sample without any specific analytical instrumentation.

SUMMARY OF THE INVENTION

In one aspect, the invention is directed to an optical disk, adapted to be read by an optical reader, comprising a first sector having a substantially self-contained assay means for binding an analyte suspected of being in a sample to at least one
5 predetermined location in the first sector and a second section containing control means for conducting the assay and analyte location information, with respect to one or more analytes suspected of being in the sample, accessible to the reader, wherein the presence or absence of the analyte at said location is determinable by the reader using the control means and the location information. Depending on the nature of the
10 assay, the disk may include fluid storage means, fluid transfer means, such as one or more capillary ducts, valves, batteries, dialyzers, columns, filters, sources of electric fields, wires or other electrical conductive means such as metallic surface deposits and the like.

The disk may have one or more sample entry ports to deliver sample fluid to
15 the assay sector. Such ports if present are preferably sealable so that after application of the sample to the disk, the sealed disk including the sample comprises a hermetically sealed device that may be conveniently disposed of by conventional means or other disposal mechanisms for dealing with biological waste. Also, the assay sector of the disk is conveniently divided into various subsections for sample
20 preparation and analyte separation. A waste receptacle subsection may be conveniently provided as well. The assay sector may be divided into a multiplicity of subsectors that each receives a sample. Each such subsector may analyze for one or more analytes depending on the particular application at hand.

In another aspect the invention is directed to an apparatus for conducting an
25 assay comprising an optical disk, a disk reader and an information processor, the disk comprising a first sector having substantially self-contained assay means for localizing an analyte suspected of being in a sample to at least one, predetermined location in the

first sector and a second sector containing control information for conducting the assay and analyte location information, with respect to one or more analytes suspected of being in the sample, accessible to the reader and processable by the information processor, wherein the disk is adapted to be read by the reader and the information processor is adapted to determine the presence or absence of the analyte at said location using the control information and the location information. The apparatus may include a reader having a CD-ROM or DVD reader and an information processor, such as a personal computer.

In still another aspect the invention is directed to an optical disk, adapted to be read by a CD-ROM or DVD reader, comprising a substantially self-contained assay means in the disk for localizing an analyte suspected of being in a sample to at least one, predetermined location on the disk and means at said location for detection of the absence or presence of the analyte by the CD-ROM or DVD reader.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic representation of a disk of this invention.

Figure 2 A is a more detailed schematic representation of a sample preparation and assay sector of the disk, illustrating the overall layout of a typical assay sector.

Figure 2 B is a schematic representation of an ubiquitous assay sector that is capable of performing immunoassays, DNA testing, cell counting, spectrophotometric assays and electrolyte analysis.

Figure 3 is a schematic representation of a disk of this invention illustrating a multiplicity of assay sectors, each having an individual sample inlet port.

Figure 4 is a more detailed schematic representation of one of the assay sectors illustrated in Fig. 3.